

(12) INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(19) World Intellectual Property Organization
International Bureau



(43) International Publication Date
4 January 2001 (04.01.2001)

PCT

(10) International Publication Number
WO 01/00118 A1

(51) International Patent Classification⁷: **A61F 13/08**

[US/US]; Route 1, Box 369-D, Germantown, NC 27109 (US).

(21) International Application Number: PCT/US00/17213

(22) International Filing Date: 23 June 2000 (23.06.2000)

(74) Agents: CALKINS, Charles, W. et al.; Kilpatrick Stockton LLP, 1001 West Fourth Street, Winston-Salem, NC 27101 (US).

(25) Filing Language: English

(26) Publication Language: English

(30) Priority Data:
60/141,085 25 June 1999 (25.06.1999) US

(81) Designated States (*national*): AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BY, BZ, CA, CH, CN, CR, CU, CZ, DE, DK, DM, DZ, EE, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NO, NZ, PL, PT, RO, RU, SD, SE, SG, SI, SK, SL, TJ, TM, TR, TT, TZ, UA, UG, US, UZ, VN, YU, ZA, ZW.

(71) Applicant (*for all designated States except US*): CAROLON COMPANY [US/US]; 601 Forum Parkway, Rural Hall, NC 27045 (US).


(84) Designated States (*regional*): ARIPO patent (GH, GM, KE, LS, MW, MZ, SD, SL, SZ, TZ, UG, ZW), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, CH, CY, DE, DK, ES, FI, FR, GB, GR, IE,

(72) Inventor; and

(75) Inventor/Applicant (*for US only*): REID, Lawrence

[Continued on next page]

(54) Title: MULTILAYER COMPRESSION STOCKING SYSTEM AND METHOD



(57) Abstract: A multilayer compression stocking or bandage system comprises a plurality of layers, including an underlayer and at least one overlay, each of which may have predetermined amounts of compressive pressure at discrete locations. In one aspect, the underlayer has one or more alignment markings, each positioned at a different location on the underlayer to assist in aligning discrete locations of compressive pressure on the lower extremities. In another aspect, each of the layers has one or more alignment markings, each alignment marking positioned at a different location on the respective layer, and each alignment marking on a layer corresponds to a different one of the alignment markings on each other layer. When alignment markings on each layer are aligned with corresponding markings on each other layer, discrete locations of specific amounts of compressive pressure on each layer can be properly aligned, resulting in accurate higher pressures at particular anatomical locations and proper pressure gradations along the length of the leg.

WO 01/00118 A1



IT, LU, MC, NL, PT, SE), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, GW, ML, MR, NE, SN, TD, TG).

For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.

Published:

- *With international search report.*
- *Before the expiration of the time limit for amending the claims and to be republished in the event of receipt of amendments.*

MULTILAYER COMPRESSION STOCKING SYSTEM AND METHOD

The present application claims the benefit, under 35 U.S.C. § 119, of U.S.
5 provisional application serial number 60/141,085, filed June 25, 1999.

FIELD OF THE INVENTION

The present invention relates to elastic garments or wraps that exert a compressive
force when worn. An aspect of the invention is a compression stocking useful in the
10 prevention and/or treatment of medical conditions of the lower extremities and vascular
system in the lower extremities.

BACKGROUND OF THE INVENTION

Therapeutic garments and elastic bandages that exert a compressive force are often
15 utilized in the prevention and therapy of lower extremity vascular system disorders, such
as edema, emboli, and thrombophlebitis. For example, compressive stockings are utilized
to improve vascular circulation and to reduce edema and the possibility of emboli in the
legs. Compression therapy is often utilized for the prevention and treatment of conditions
caused by chronic venous insufficiency, including stasis ulceration in the leg. Elastic
20 bandages, for example, have traditionally been used for compressive therapy of vascular
disorders, including ulcers, of the lower extremities.

Therapeutic or compressive stockings are constructed to apply compressive
pressure to a wearer's legs. Compressive pressure may be greatest at the foot and
gradually decrease from the foot towards the upper, or proximal, part of the leg.
25 Alternatively, compressive pressure may be greatest at the ankle and gradually decrease
towards the upper part of the leg. The amount of compressive pressure applied depends on
the particular use and needs of the wearer. In order to achieve the intended preventative
and/or therapeutic effect and to avoid complications of compressive pressure intervention,
compressive pressure must be applied accurately. For example, should a greater amount
30 of compressive pressure be applied higher on the leg than lower on the leg, blood flow
may be impaired with a possible tourniquet effect occurring.

Further details on therapeutic compressive stockings, their use and construction, may be found in U.S. Patent Nos. 4,015,448, issued April 5, 1977; 4,172,456, issued October 30, 1979; 4,513,740, issued April 30, 1985; 4,745,917, issued May 24, 1988; and 5,005,567, issued April 9, 1991. The disclosure of each of these patents is hereby
5 incorporated herein by reference.

When elastic bandages are used, the bandages are wrapped onto the leg with the greatest pressure at the foot or ankle, and compressive pressures are manually reduced as the bandages are wrapped up the leg. Applying correct pressures at particular locations, and properly graduating pressures, so as to avoid creating a tourniquet effect when
10 wrapping elastic bandages is difficult. Elastic bandages also come in a variety of styles, with stretch characteristics varying widely from product to product, making proper application of correct compression difficult.

The compressive pressure applied by stockings at a particular anatomical location may be determined and measured by various techniques. As will be recognized in the art,
15 there is no standardized system for testing and measuring compressive pressures. A commonly used system for measuring compressive pressures is a British system, which may be used with pressure testing equipment made by Instron and by Hatra. (*See*, British Standard Specification for Graduated Compression Hosiery, BS 6612: 1985.) The British system divides compressive pressures into three levels, each level being referred to as a
20 class. In Class I, 14 to 19 mm Hg (millimeters of mercury) of compressive pressure is provided. In Class II, 18 to 25 mm Hg of compressive pressure is provided. In Class III, 24 to 35 mm Hg of compressive pressure is provided. A Class I stocking would therefore provide 14 to 19 mm Hg of compressive pressure at the point of greatest compressive
25 pressure. A Class II stocking would provide 18 to 25 mm Hg of compressive pressure at the point of greatest compressive pressure, and a Class III stocking would provide 24 to 35 mm Hg compressive pressure at the point of greatest compressive pressure. Suggested preventative and therapeutic uses for each class of pressure are also defined by the British system. Another system for measuring compressive pressures is a German system, which may be used with testing equipment made by Holenstein. The German system categorizes
30 compressive pressures between 20 and 30 mm Hg as Class I, between 30 and 40 mm Hg

as Class II, and between 40 and 50 mm Hg as Class III. (*See also*, European Committee for Standardization, CEN-TC 205WG2 Medical Compression Hosiery.)

There are no recognized standards for testing elastic bandages to accurately determine compressive pressures. Pressures applied by elastic bandages have been described by the amount of stretch of the elastic material, such as 50%, 100%, and 200%. Controlling the amount of compressive pressure a bandage will exert when applied requires extensive technical knowledge of bandage stretch characteristics, as well as experience. Some elastic bandages have incorporated methods to assist a care-giver in proper application. For example, visual indicators may be used to signify the degree of stretch, and thus compressive force, provided by an elastic bandage. A continuous pattern of geometric shapes may be formed on an elastic bandage by using indicator yarns or with print. Either the shape of the geometric design or the spacing between shapes in a pattern may change when tension is applied to the bandage, indicating a change in compressive force. Such designs in elastic bandages have been used to indicate compressive pressures as high as 40 to 50 mm Hg.

Compressive stockings, due to the compressive pressures they apply, are generally more difficult to place on the leg than conventional dress hosiery. To be most effective, the area or areas of the stockings having the highest compressive pressure, and thus the most difficult to apply, should be located at the feet or more distal portions of the leg, such as the ankle. Consequently, compressive stockings are often especially difficult for the elderly or persons with compromised mobility to apply to their legs. In addition, higher compressive pressures are indicated for the prevention and treatment of leg ulcerations. As a result, compressive stockings that use higher compressive pressures, such as for leg ulcerations, may be even more difficult to apply.

It has been generally found that most persons can place, or apply, Class I stockings with minimal or no assistance. However, many patients are unable to apply or remove stockings with Class II or Class III pressures without assistance by a care-giver or medical personnel. Such stockings may also be difficult for the care-giver to apply. As discussed above, compression therapy is often utilized for the prevention and treatment of ulcers, for which Class II or Class III compressive pressures may be beneficial. Often, patients suffering from leg ulcers have difficulty applying stockings with Class II or Class III

compressive pressures due to age or disability, such as compromised mobility. Such patients may also have difficulty removing such stockings, particularly if they are applied by a care-giver. It may also be difficult for a care-giver to remove such stockings due to the compressive pressures involved.

5 For compressive therapy to be most effective, higher pressures may be required. The very high pressures that may be required for both prevention and therapy may preclude use of a stocking, as construction of a stocking having such higher compressive force may cause the stocking to be too tight to apply over the heel of a person's foot. As an alternative, high pressure elastic bandages which can be applied directly to a leg,
10 without placement over the foot as with compressive stockings, may be used. Pressures higher than those supplied by a stocking can be applied by an elastic bandage. Using a high pressure elastic bandage, a leg is generally wrapped by a care-giver, rather than by a patient, as applying desired pressures with proper pressure graduation up the leg requires training and experience. Because of the difficulty of properly applying elastic bandages,
15 they may be left on a patient for longer periods than a compressive stocking.

Higher compressive pressures and a wider range of pressures can be obtained by utilizing multiple stockings in layers. The layering of compressive pressures will produce a cumulative pressure effect. Layering a stocking that provides 10 mm Hg pressure with a Class I stocking would produce a stocking with Class II pressure. Layering a stocking that
20 provides 10 mm Hg pressure with a Class II stocking would produce a stocking with Class III pressure. Layering two Class I stockings may produce Class II compressive pressures. Similarly, applying a Class II stocking over a Class I stocking may produce Class III compressive pressures. Layering of stockings allows the use of higher compressive pressures indicated for certain medical conditions. Since compression stockings are
25 constructed having specific compressive pressures, layering of stockings to achieve specific higher, cumulative, compressive pressures eliminates the uncertainty of pressures resulting from application of elastic bandages. In addition, using multiple layers of compression stockings, patients and care-givers can apply a wide variety of accurate pressures.

30 However, there are many problems associated with layering multiple stockings. One problem is that it is difficult to coordinate the compressive pressures applied by each

stocking to achieve a desired increased pressure at particular anatomical locations on the lower extremities. Should the areas of compressive pressure not align correctly, it is possible that the area of highest pressure may be on a more proximal, and thus undesired, area of the leg, and a tourniquet effect may result. Further, any ridges or wrinkles in the stockings, introduced either during construction of the stockings or as the stockings are applied, may cause discomfort to the wearer and/or produce an undesired localized pressure point on the skin of the wearer. Because high pressures are often required, such ridges could also eventually cause or exacerbate skin break down and result in ulcerations and other compromise of vascular flow and/or tissue integrity. When elastic bandages are used, the bandages overlap when applied, or may overlap more as they are worn, and create a localized pressure point that may cause skin irritation, breakdown, and ulceration.

Accordingly, there remains a need for compression stockings that are able to accurately achieve Class II, Class III, or greater compressive pressures at particular anatomical locations with proper pressure gradations and a smooth surface against the skin, while being easier to apply, than compression stockings and elastic compression bandages currently available. There is also a need for higher pressure compression stockings that are easier to correctly apply and that can be made efficiently and economically.

These needs, as well as other needs, are met by the present invention.

SUMMARY OF THE INVENTION

The present invention provides compression garments and bandages that overcome the disadvantages of currently available compression garments and elastic compression bandages and provide advantages to the wearer and care-giver.

One aspect of the present invention is a multilayer compression stocking system for use on a person's lower extremities. The compression stocking system comprises a plurality of layers including an underlayer and at least one overlayer. The underlayer may be worn next to the skin or over another stocking, bandage or garment and includes predetermined amounts of compressive pressure at discrete locations. The underlayer further includes alignment markings to assist a wearer in positioning the underlayer on

their leg. The alignment markings may be located at the locations of compressive pressure or at different locations on the underlayer.

The overlayer or overlayers is/are applied over the underlayer. As discussed below with reference to other aspects and embodiments of the present invention, one or
5 more of the overlayers may include alignment markings that may or may not correspond to the alignment markings on the underlayer. In an embodiment of the present invention, the overlayer is aligned simply by aligning the toe and heel portions of the underlayer and the overlayer. In alternative embodiments, as discussed below, alignment markings are utilized to align the overlayer and underlayer.

10 The overlayer may or may not include areas of compressive pressure depending on the application. The uppermost overlayer may be constructed and/or colored to having a pleasing cosmetic appearance.

Further details of possible embodiments of the underlayer and the overlayer are set forth below with reference to additional embodiments of the present invention.

15 Another aspect of the present invention is a multilayer compression stocking system comprising: a first layer, or underlayer, providing a predetermined amount of compressive pressure; at least one overlayer providing a predetermined amount of compressive pressure; and each layer including an alignment marking or markings so that the layers may be aligned, thereby aligning the areas of compressive pressure.

20 Predetermined compressive pressures for each layer may be less than Class I pressure and may be Class I, Class II, and/or Class III pressures, or higher. More than one overlayer may be utilized to produce the compressive pressures desired. For example, an underlayer and additional overlayers may be layered to provide a total compressive pressure in a Class I range. As another example, an underlayer and two additional layers, each
25 providing Class I compressive pressures, may be utilized to achieve Class III compressive pressures. The overlayer may be colored and/or constructed to provide an attractive appearance. For example, an overlayer may be provided in colors and/or patterns of conventional dress hosiery.

30 As will be recognized in the art, there is no standardized system for testing and measuring compressive pressures. The compressive pressure applied by stockings at a particular anatomical location may be determined and measured by various techniques. A

commonly used system for measuring compressive pressures is a British system, which may be used with pressure testing equipment made by Instron and by Hatra. The British system divides compressive pressures into three levels, each level being referred to as a class. In the British system, Class I provides 14 to 19 mm Hg of compressive pressure.

5 Class II provides 18 to 25 mm Hg of compressive pressure, and Class III provides 24 to 35 mm Hg of compressive pressure. Thus, at the point of greatest compressive pressure, a Class I stocking would provide 14 to 19 mm Hg of compressive pressure, a Class II stocking would provide 18 to 25 mm Hg of compressive pressure, and a Class III stocking would provide 24 to 35 mm Hg compressive pressure. Suggested preventative and
10 therapeutic uses for each class of pressure are also defined by the British system. Another system for measuring compressive pressures is a German system, which may be used with testing equipment made by Hohenstein. The German system categorizes compressive pressures between 20 and 30 mm Hg as Class I, between 30 and 40 mm Hg as Class II, and between 40 and 50 mm Hg as Class III.

15 A multilayer compression stocking system of the present invention may further comprise a final outer layer without medically therapeutic compressive pressures. The final outer layer may be colored and/or constructed to provide an attractive cosmetic appearance, for example, an appearance similar to non-compressive dress hosiery.

In use, an underlayer may be applied first to a wearer's leg and then an overlayer
20 applied up and over the underlayer. Alignment markings on each layer may then be aligned to create the desired areas and amounts of compressive pressure and to ensure that the pressures are properly graduated, for example, in decreasing amounts up the leg. A final outer layer, if utilized, may then be applied up and over the compressive underlayer and overlayer.

25 A multilayer compression stocking of the present invention may be produced utilizing a circular knitting machine. Suitable yarns and knitting techniques include those set forth in the patents referred to above and incorporated herein by reference. It is generally preferable to construct the stocking without seams. Seamless construction provides the advantage of avoiding ridges or wrinkles, which may lead to deterioration of
30 the skin. The multilayer compression stocking may be produced in different sizes, both in length and circumference, for use by a wide variety of people. Pressures graduations along

the length of each layer would preferably be constructed the same so that the pressures are matched at the same location on each layer, ensuring the proper cumulative pressure effect and the proper pressure gradation when applied to a leg. The multilayer compression stocking may be any size, style, or length. For example, the multilayer compression
5 stocking may be of knee length, or may extend above the knee in mid-thigh length, full-thigh length, or may be pantyhose. The underlayer could also be of a different length than the outer layer or layers. For example, the underlayer could be of knee length with the outer layer or layers thigh length.

A further aspect of the present invention is a multilayer compression bandage
10 system. The bandage system comprises a plurality of layers including an underlayer and at least one overlayer. The underlayer may be worn next to the skin or over another bandage or garment and includes predetermined amounts of compressive pressure at discrete locations. The underlayer further includes alignment markings to assist a wearer in positioning the underlayer on their body. The alignment markings may be located at the
15 locations of compressive pressure or at different locations on the underlayer.

The overlayer or overlayers is/are applied over the underlayer. As discussed below with reference to other aspects and embodiments of the present invention, one or more of the overlayers may include alignment markings that may or may not correspond to the alignment markings on the underlayer. In an embodiment of the present invention, the
20 overlayer is aligned simply by aligning the top and bottom portions of the underlayer and the overlayer. In alternative embodiments, as discussed below, alignment markings are utilized to align the overlayer and underlayer.

The overlayer may or may not include areas of compressive pressure depending on the application. The uppermost overlayer may be constructed and/or colored to having a
25 pleasing cosmetic appearance.

Further details of possible embodiments of the underlayer and the overlayer are set forth below with reference to additional embodiments of the present invention.

A further aspect of the present invention is a multilayer compressive bandage system comprising: a first layer, or underlayer, providing a predetermined amount of
30 compressive pressure; at least one overlayer providing a predetermined amount of compressive pressure; and each layer including an alignment marking or markings so that

the layers may be aligned, thereby aligning the areas of compressive pressure.

Predetermined compressive pressures for each layer may be less than Class I pressure and may be Class I, Class II, and/or Class III pressures, or higher. More than one overlayer may be utilized to produce the compressive pressures desired. For example, an underlayer
5 and two additional layers, each providing Class I compressive pressures, may be utilized to achieve Class III compressive pressures. The overlayer may be colored and/or constructed to provide an attractive appearance. For example, an overlayer may be provided in colors and/or patterns of conventional dress hosiery.

A multilayer compressive bandage system of the present invention may further
10 comprise a final outer layer without medically therapeutic compressive pressures. The final outer layer may be colored and/or constructed to provide an attractive cosmetic appearance.

As will be understood by those of ordinary skill in the art, a multilayer
compressive of the present invention may be utilized in multiple areas on a patient,
15 including, but not limited to the leg; including upper and lower legs; foot; arm, including upper and lower arms; hand; torso; head and other locations where compression is desired. The amount of compressive force exerted by the multilayer compression bandage may be varied as described herein so as to provide the degree of compressive force desired at a particular location.

20 An advantage of the present invention is that a layering system allows a person to receive more compressive pressure than otherwise possible.

Another advantage of the present invention is that alignment markings or areas
allow different layers to be correctly aligned to provide the desired compressive pressures
at particular anatomical locations and proper pressure gradations along the length of the
25 leg.

Another advantage of the present invention is that easier placement of compression
stockings with higher total compressive pressures is allowed by the use of layers. As a
result of such easier placement, compliance with use of higher pressure compression
stockings as part of a medical regimen by elderly persons and those with compromised
30 strength or mobility is enhanced.

Another advantage of the present invention is higher pressure compression stockings that are easier to correctly apply can be made efficiently and economically. An underlayer stocking is preferably constructed from nylon-covered spandex yarns alternating with relatively fine count nylon yarns to enhance ease of application by
5 reducing friction and to reduce wrinkling upon application of the overlayer or overlayers.

An underlayer stocking is preferably constructed with mild or little compressive pressure in the toe area. Toe construction is preferably of a durable nylon yarn in the size range of fine to medium denier, or is reinforced through knitting techniques, to reduce the chance of cutting by toe nails. Construction with mild or little compressive pressure will
10 generally decrease the risk of undesired pressure and reduce the chance of skin breakdown on the ends of the toes. The toe area is preferably constructed of high stretch modulus yarns so that the area will conform to the shape of the toes.

The instep of the underlayer stocking will generally be constructed to provide more compressive pressure than the toe area. Preferably the underlayer is constructed so that
15 there is a smooth transition in material between the toe area and the instep area, without ridges, to minimize the chance of producing an undesired localized pressure point on a wearer's skin. A smooth transition in construction may be accomplished, for example, by programming a knitting machine to enable a gradual change from one compression level to another, thereby eliminating a sharply defined line of pressure differential in the stocking.

To further reduce the chance of skin breakdown and to reinforce the stocking
20 fabric, yarns with high strength and low coefficient of friction properties, such as Teflon, can also be incorporated into the fabric. Areas of the stocking including the toe, the top of the instep, and the heel may be reinforced in such a manner.

The heel area and ankle area of the underlayer stocking are preferably visually
25 marked. Suitable marking techniques include using a knitted-in colored yarn, of a different color than the base yarn; a knit change; or marking by printing or applying a color to the heel area. Marking of the heel and ankle areas will assist in the alignment of the underlayer by allowing the marked heel area of the underlayer to be properly positioned on a wearer's foot.

Knitting between the toe area and the heel area of the underlayer will preferably
30 reflect the anatomical shape of the foot in that area. Knitting between the ankle and calf

will reflect the anatomical shape of the leg; for example, a typical hourglass shape may be utilized.

An underlayer stocking is preferably constructed so that it has compressive pressures in desired locations, including, the instep, heel, ankle, calf, knee, and/or thigh.

5 Compressive pressures will generally gradually reduce from the distal portion of the stocking towards the proximal, or upper, portion of the stocking.

In order to facilitate correct placement of the underlayer stocking on the leg of a wearer, the stocking would be preferably knitted with yarns, and in a manner, so as to provide stretch in both the horizontal and vertical directions (i.e., at least two-way stretch).

10 This feature will permit the stocking fabric to adjust for minor variations in anatomy in the ankle and/or knee areas.

As described above, according to the present invention, a multilayer compression stocking includes alignment markings to permit each stocking layer to be correctly placed on the wearer, and with respect to other stocking layers, so as to achieve the desired
15 compressive pressure in the desired areas of the stocking and thus at desired locations on the leg of the wearer. The alignment markings may comprise a different color yarn, a knit change, printing, and/or other markings to differentiate discrete locations on a stocking. For example, during construction of a compressive pressure of the stocking, the knitting machine could be programmed to insert a yarn or provide a knit change at a desired
20 location to produce an alignment marking. Preferably, the alignment marking will not introduce a rib or other wrinkle in the stocking layer that could cause a localized pressure point on a wearer's skin.

In general, it may be preferable for at least one set of alignment markings to correspond, or be located near, areas of greatest compressive pressure in a stocking. Thus,
25 for example, alignment markings may be located near the heel and/or ankle region of each stocking layer. To facilitate and increase alignment, additional sets of alignment markings could be located in other areas, for example, the calf, instep, or other portions of the stocking. As an example, if pressure graduations are the same in each layer as preferred, alignment of the tops of the stocking layers, such as the tops of knee-length stocking
30 layers, could also provide proper placement of stockings.

Additional stocking layers may be similar to the underlayer, with appropriate alignment markings and pressure characteristics and produced in similar manners. A final outer stocking layer may be colored and/or knitted in a fashion to provide an attractive cosmetic appearance. For example, a final outer stocking layer may be provided in colors and/or patterns of conventional dress hosiery.

An overlayer stocking is preferably constructed so that areas of compressive pressure have pressure characteristics and gradation that match the pressure characteristics and gradation of an underlayer. As an example, when compressive pressure is greatest at the ankle area for the underlayer, the greatest compressive pressure for the overlayer is preferably also at the ankle area, and both underlayer and overlayer are preferably aligned with each other and at the same place on the wearer's ankle. As discussed above, should the pressures along the length of the leg be misaligned, accurate placement of specifically desired higher pressures may not be achieved, resulting in a less effective stocking system, and a tourniquet effect could occur.

As will be realized from the foregoing discussion, the stocking layers in the system of the present invention may comprise separate articles. Alternatively, each of the stocking layers may be joined to create a multilayer compression stocking comprising a single article. For example, the multiple layers may be joined in the toe region.

A multilayer compression stocking of the present invention may be applied by first positioning the underlayer on the leg of a wearer. Each overlayer is then positioned over the underlayer, or the layer immediately underneath, by matching the toes, heels, alignment markings, and tops of the layers. Such successive placement of stocking layers by aligning like areas and alignment markings ensures proper positioning of compressive pressures in desired locations.

In the present invention, an underlayer may comprise a stocking with visually distinctive alignment markings in the toe, heel, and top areas. A distinctive visual appearance may be obtained, for example, through coloring, use of colored yarn, and/or a knitting change. An underlayer may additionally comprise an alignment marking, for example, at the most narrow point of the ankle. Use of the ankle alignment marking, and visually distinctive heel, toe, and top areas allow the underlayer to be properly positioned on a person's lower extremity.

An overlayer stocking may include visually apparent markings similar to those of an underlayer. Alternatively, an overlayer may include a visually distinctive heel region only. Alignment of the heel region and top of an overlayer with the heel region and top of an underlayer may provide sufficient alignment of the layers for a variety of applications.

5 Similar techniques may be utilized in the production and use of a multilayer compression bandage of the present invention. In certain embodiments, a non-circular knitting machine may be employed to produce multilayer compression bandages suitable for wrapping.

Those of ordinary skill in the art will appreciate the advantages and features of the present invention as described above and as is apparent from the detailed description
10 below. As will be realized by those of skill in the art, many different embodiments of a multilayer compression stocking system according to the present invention are possible. Preferred embodiments of a multilayer compression stocking system will include one or more of the following features.

BRIEF DESCRIPTION OF THE DRAWINGS

FIGURE 1 is a perspective view of an embodiment of a compression stocking underlayer of the present invention.

FIGURE 2 is a perspective view of an embodiment of a compression stocking
20 overlayer of the present invention.

FIGURE 3 is a perspective view of an embodiment of a compression stocking underlayer and overlayer of the present invention, illustrating an overlayer bottom foldably attached to an underlayer top.

FIGURE 4 is a perspective view of the embodiment of the multilayer compression
25 stocking of Figure 3 with the overlayer folded over the underlayer.

DETAILED DESCRIPTION

Systems and methods of a multilayer compression stocking and/or bandage according to the present invention provide a layering system that allows a person to
30 receive higher compressive pressures, that can be correctly aligned to provide the desired

compressive pressures at particular anatomical locations and proper pressure gradations along the length of the leg, and that can be applied with greater ease.

An example of an embodiment of the present invention is a multilayer compression stocking system comprising an underlayer and at least one overlayer, each of the layers having predetermined amounts of compressive pressure as discrete locations on the respective layer. Such an embodiment also includes at least one alignment marking on each layer. If multiple alignment markings are used, each marking may be positioned at a different location on a layer. Alignment markings on different layers correspond with similarly positioned alignment markings on each other layer, and, as such, can be aligned with corresponding markings on each other layer.

Figures 1 and 2 illustrate an embodiment of a multilayer compression stocking system according to the present invention, including underlayer 20 (Fig. 1) and overlayer(s) 30 (Fig. 2). As shown in Figure 1, underlayer 20 may comprise a stocking with visually distinctive alignment markings in the toe 11, heel 13, ankle 14, and proximal 19 areas. A distinctive visual appearance of alignment markings may be obtained, for example, through use of different colored yarns, a knitting change, printing, and/or colored markings. An underlayer may additionally comprise an alignment marking (24), for example, at the most narrow point of the ankle (14). Use of visually distinctive alignment markings of the toe 21, heel 23, ankle 24, and top 25 allow the underlayer to be properly positioned at the proper anatomical locations on a person's lower extremity.

Toe alignment markings 21 and 31 are positioned at the same location in toe area 11 on each of the underlayer 20 and overlayer(s) 30, respectively. In similar fashion, heel alignment markings 23 and 33 are positioned at the same location in heel area 13 on each of the underlayer 20 and overlayer(s) 30, respectively. Likewise, ankle alignment markings 24 and 34 are positioned at the same location in ankle area 14 on each of the underlayer 20 and overlayer(s) 30, respectively.

In such an embodiment, as illustrated in Figs. 1 and 2 together, for example, alignment of alignment markings 31, 33, and 34 on overlayer(s) 30 with corresponding markings 21, 23, and 24 on underlayer 20 allows accurate alignment of discrete locations of compressive pressure on each layer. As a result, specific higher cumulative pressures can be accurately applied to particular anatomical locations on a leg.

In an alternative embodiment, an overlayer may include a visually distinctive heel region 13 only. In such an embodiment, alignment of the heel region 13 and top 35 of overlayer 30 with the heel region 13 and top 25 of an underlayer 20 may provide sufficient alignment of the layers for a variety of applications.

5 Systems and methods of an embodiment of the present invention may also comprise pressure graduations along the length of each of underlayer 20 and overlayer(s) 30. Pressure graduations are preferably the same along the length of each layer such that compressive pressures can be matched at each anatomical location, for example, at instep 12, heel 13, ankle 14, calf 15, knee 16, and thigh 17. Aligning the same pressure
10 graduations along the length of each layer can also ensure the proper cumulative pressure graduation along the length of a layered stocking system when the layers are applied to a leg.

An embodiment of the present invention may also include the greatest amount of compressive pressure at a predetermined distal portion of each of the underlayer and
15 overlayer(s). In addition, one of the alignment markings of each of the underlayer and overlayer(s) may be located at a predetermined area of greatest compressive pressure. Referring to Figs. 1 and 2, underlayer 20 and overlayer(s) 30 may be constructed so as to provide the greatest amount of compressive pressure at distal portion 18. Ankle alignment markings 24 and 34 would thus be located at the predetermined area of greatest
20 compressive pressure on each of the underlayer 20 and overlayer(s) 30. By aligning alignment markings 24 and 34, the greatest amount of compressive pressure at predetermined distal portion 18 of each of the underlayer and overlayer(s) would be aligned, further ensuring that the amounts of compressive pressure decrease from
predetermined distal portion 18 to proximal portion 19 along the length of a wearer's leg.

25 In an embodiment of a multilayer compression stocking system of the present invention, predetermined amounts of compressive pressure of each of the underlayer 20 and overlayer(s) 30 may comprise less than Class I pressure, Class I, Class II, and/or Class III pressures, or higher compressive pressures, as described above. Layering of compressive pressure stockings in a multilayer compression stocking system will produce
30 a cumulative pressure effect and allow higher compressive pressures when applied to a wearer's leg than otherwise attainable.

With higher compressive pressures attainable in a multilayer compression stocking system, construction of the layers may include features to reduce the risk of localized pressure points on a wearer's skin. For example, each of the underlayer 20 and overlayer(s) 30 may comprise a toe portion 11 constructed with mild or little compressive pressure and having a high stretch modulus so that toe area 11 will conform to the shape of the wearer's toes. Each of the layers may also comprise construction having at least a two-way stretch. For example, providing for stretch in both the horizontal and vertical directions will allow the stocking fabric to adjust for minor variations in anatomy in ankle area 14 and knee area 16. Each of the layers may also comprise construction having the shape of the anatomy of the lower extremities, including toe 11, instep 12, heel 13, ankle 14, calf 15, knee 16, and thigh 17, to provide for a smoother, more conforming fit of each stocking layer.

Each of the underlayer 20 and overlayer(s) 30 preferably have seamless construction. In particular, construction in and between toe area 11 and instep area 12 of each layer should be smooth so as to decrease any risk of localized pressure points which may lead to skin breakdown.

While underlayer 20 and overlayer 30 are depicted as full-thigh length layers, stockings of knee-length, mid-thigh length, and pantyhose length may also be utilized in accordance with the present invention.

In an alternative embodiment, each of the underlayer 20 and overlayer(s) 30 may be constructed so as to be joined in the toe portion 11. Such an arrangement would facilitate keeping the multiple layers together so that matching layers would be used in conjunction with each other each time they are applied.

In an embodiment of a multilayer compression stocking system of the present invention, one of the overlayer(s) 30 may be an outermost overlayer. Such an outermost layer may be colored and/or constructed to provide an attractive cosmetic appearance. In an alternative embodiment, a non-compressive final outer layer may be placed over the outermost overlayer. Such a non-compressive final outer layer may be colored and/or constructed to provide an attractive cosmetic appearance.

Figures 3 and 4 illustrate an embodiment of a multilayer compression stocking system according to the present invention, including an overlayer 50 foldably attached to

an underlayer 40. As shown in Figure 3, underlayer 40 may comprise a knee-length stocking with visually distinctive alignment markings in the toe 11, heel 13, ankle 14, and calf 15 areas. A distinctive visual appearance of alignment markings may be obtained, as described above, through use of different colored yarns, a knitting change, printing, and/or colored markings, for example. An underlayer may additionally comprise an alignment marking (44A), for example, at the most narrow point of ankle 14. Use of visually distinctive toe 41, heel 43, ankle 44A, and knee 45 alignment markings allow the underlayer to be properly positioned at the corresponding anatomical locations on a person's lower extremity.

In Fig. 3, underlayer 40 is shown as having a top 46 in proximal area 19A. Overlayer 50 is shown as having a bottom 51 in proximal area 19B, and a top 52 at distal portion 18B. Bottom 51 of overlayer 50 is attached to top 46 of underlayer 40 at knee alignment marking 45.

Figure 4 depicts overlayer 50 folded down and in position over underlayer 40. To achieve proper therapeutic positioning, top 52 of overlayer 50 is folded downwardly so that ankle alignment marking 44B of overlayer 50 aligns with ankle alignment marking 44A of underlayer 40. As such, ankle alignment markings 44A and 44B are aligned at the same location in ankle area 14.

In such an embodiment, as illustrated in Figs. 3 and 4, for example, positioning knee alignment marking 45 above calf 15 and aligning ankle alignment markings 44A and 44B in ankle area 14 allows accurate alignment of discrete locations of compressive pressure on each layer. As a result, specific higher cumulative pressures can be accurately applied to particular anatomical locations on a leg.

Systems and methods of an embodiment of the present invention, as illustrated in Figs. 3 and 4, may also comprise pressure graduations along the length of each of underlayer 40 and overlayer 50. Pressure graduations are preferably the same along the length of each layer such that compressive pressures can be matched at specific anatomical locations, for example, at ankle 14 and calf 15. Aligning the same pressure graduations along the length of each layer can also ensure the proper cumulative pressure graduation along the length of a layered stocking system when the layers are applied to a leg.

An embodiment of the present invention may also include the greatest amount of compressive pressure at a predetermined distal portion of each of the underlayer and overlayer. In addition, one of the alignment markings of each of the underlayer and overlayer may be located at a predetermined area of greatest compressive pressure.

5 Referring to Figs. 3 and 4, underlayer 40 and overlayer 50 may be constructed so as to provide the greatest amount of compressive pressure at distal portions 18A and 18B, respectively. Ankle alignment markings 44A and 44B would thus be located at a predetermined area of greatest compressive pressure on each of the underlayer 40 and overlayer 50. By aligning alignment markings 44A and 44B, the greatest amount of
10 compressive pressure at predetermined distal portions 18A and 18B of the underlayer 40 and overlayer 50, respectively, would be aligned, further ensuring that the amounts of compressive pressure decrease from predetermined distal portions 18A and 18B to proximal portions 19A and 19B along the length of a wearer's leg.

In an embodiment of a multilayer compression stocking system of the present
15 invention, predetermined amounts of compressive pressure of each of the underlayer 40 and overlayer 50 may comprise less than Class I pressure, Class I, Class II, and/or Class III pressures, or higher compressive pressures, as described above. Layering of compressive pressure stockings in a multilayer compression stocking system will produce a cumulative pressure effect and allow higher compressive pressures when applied to a wearer's leg than
20 otherwise attainable.

With higher compressive pressures attainable in a multilayer compression stocking system, construction of the layers may include features to reduce the risk of localized pressure points on a wearer's skin. For example, each of the layers may also comprise construction having at least a two-way stretch to allow for minor variations in anatomy, as
25 in ankle area 14, as well as to facilitate downward folding of overlayer 50 over underlayer 40. The underlayer may also comprise construction having the shape of the anatomy of the lower extremities, including toe 11, instep 12, heel 13, ankle 14, and calf 15, to provide for a smoother, more conforming fit.

As discussed above, underlayer 40 and overlayer 50 would preferably have
30 seamless construction. In particular, construction in and between toe area 11 and instep

area 12 of underlayer 40 should be smooth so as to decrease any risk of localized pressure points which may lead to skin breakdown.

While underlayer 40 and overlayer 50 are depicted as knee length layers, stockings of other lengths may also be utilized in accordance with the present invention as embodied
5 in Figs. 3 and 4. As described above, an overlayer may be colored and/or constructed to provide an attractive cosmetic appearance.

An embodiment of a method of applying a multilayer compression stocking system of the present invention on a person's lower extremity may comprise: positioning on the lower extremity a compressive pressure underlayer 20 having at least one alignment
10 marking, each underlayer alignment marking positioned at a different location on the underlayer 20 and corresponding to an anatomical location on the lower extremity; aligning each underlayer alignment marking with the corresponding anatomical location on the lower extremity; positioning over the underlayer 20 at least one compressive pressure overlayer 30 having at least one alignment marking, each overlayer alignment
15 marking corresponding to a different one of the underlayer alignment markings; and aligning each overlayer alignment marking with each corresponding underlayer alignment marking. Therein, each of the underlayer 20 and overlayer(s) 30 may have predetermined amounts of compressive pressure at discrete locations, as described above. In such an embodiment, where one of the overlayer(s) 30 is an outermost overlayer, the present
20 invention may further comprise positioning a non-compressive final outer layer over the outermost overlayer.

Another embodiment of a method of applying a multilayer compression stocking system of the present invention on a person's lower extremity may comprise: providing a compressive pressure underlayer 40 having a top 46 and at least one alignment marking,
25 each underlayer alignment marking positioned at a different location on the underlayer and corresponding to a different anatomical location on the lower extremity; positioning the compressive pressure underlayer 40 on the lower extremity; aligning each underlayer alignment marking, for example ankle alignment marking 44A, with the corresponding anatomical location, for example ankle 14, on the lower extremity; providing a
30 compressive pressure overlayer 50 having a top 52, a bottom 51, the overlayer bottom 51 foldably attached to the underlayer top 46, and at least one alignment marking, for

example ankle alignment marking 44B, each overlayer alignment marking corresponding to a different one of the underlayer alignment markings; downwardly folding overlayer 50 over the underlayer 40; and aligning each overlayer alignment marking with each corresponding underlayer alignment marking.

5 In such embodiments of methods of applying a multilayer compression stocking system according to the present invention, each of the underlayer 40 and overlayer 50, for example, may have predetermined amounts of compressive pressure at discrete locations. Each of the underlayer 40 and overlayer 50 may have the same pressure graduations along its respective length from distal portions 18A and 18B to proximal portions 19A and 19B,
10 so that the amounts of compressive pressure decrease from a predetermined distal portion to the proximal portion along the length of each of the underlayer 40 and overlayer 50.

 Although the present invention has been described with reference to particular embodiments, it should be recognized that these embodiments are merely illustrative of the principles of the present invention. Those of ordinary skill in the art will appreciate
15 that the system of the present invention may be implemented in other ways and embodiments. Accordingly, the description herein should not be read as limiting the present invention, as other embodiments also fall within the scope of the present invention.

What is claimed is:

1. A multilayer compression stocking system for use on a person's lower extremities, comprising:

a plurality of layers including an underlayer and at least one overlayer;

the underlayer having predetermined amounts of compressive pressure at discrete locations on the underlayer and having at least one alignment marking, each underlayer alignment marking positioned at a different location on the underlayer;

wherein the alignment markings assist the person in aligning discrete locations of compressive pressure on their lower extremities; and the overlayer is applied over the underlayer.

2. The multilayer compression stocking system of claim 1, each of the underlayer and overlayers having a length with proximal and distal portions, wherein the underlayer has pressure graduations along its length, each overlayer has pressure graduations along its length, and the pressure graduations along the length of each overlayer are the same as the pressure graduations along the length of the underlayer.

3. The multilayer compression stocking system of claim 1, wherein at least one of the underlayer and overlayers further comprises a toe portion having a high stretch modulus.

4. The multilayer compression stocking system of claim 3, at least one of the underlayer and overlayers having an instep portion, wherein each of the underlayer and overlayers further comprises a smooth construction from the toe portion to the instep portion.

5. The multilayer compression stocking system of claim 1, wherein each of the underlayer and overlayers further comprises a heel portion and one of the at least one alignment marking of the underlayer is located on the heel portion.

6. The multilayer compression stocking system of claim 1, wherein the alignment markings comprise different colored yarns, a knit change, printing, and/or colored markings.

7. The multilayer compression stocking system of claim 1, one of the at least one overlayer being an outermost overlayer, wherein the outermost overlayer is colored to provide a cosmetic appearance.

8. The multilayer compression stocking system of claim 5, wherein each of the underlayer and overlayers is joined.

9. A multilayer compression bandage system for use on a person's body, comprising:
a plurality of layers including an underlayer and at least one overlayer;

the underlayer having predetermined amounts of compressive pressure at discrete
locations on the underlayer and having at least one alignment marking, each underlayer
5 alignment marking positioned at a different location on the underlayer;

wherein the alignment marking assists the person in aligning discrete locations of
compressive pressure at a location on their body; and the overlayer is applied over the
underlayer.

10. The multilayer compression bandage system of claim 9, each of the underlayer and
10 overlayers having a length with proximal and distal portions, wherein the underlayer has
pressure graduations along its length, each overlayer has pressure graduations along its
length, and the pressure graduations along the length of each overlayer are the same as the
pressure graduations along the length of the underlayer.

11. The multilayer compression bandage system of claim 9, wherein the alignment
15 markings comprise different colored yarns, a knit change, printing, and/or colored
markings.

12. The multilayer compression bandage system of claim 9, one of the at least one
overlayer being an outermost overlayer, wherein the outermost overlayer is colored to
provide a cosmetic appearance.

20 13. The multilayer compression bandage system of claim 9, wherein each of the
underlayer and overlayers is joined.

14. A multilayer compression stocking system for use on a person's lower extremities,
comprising:

a plurality of layers including an underlayer and at least one overlayer;

25 the underlayer having predetermined amounts of compressive pressure at discrete
locations on the underlayer;

at least one of the overlayers having predetermined amounts of compressive
pressure at discrete locations on each overlayer;

the underlayer having at least one alignment marking, each underlayer alignment
30 marking positioned at a different location on the underlayer; and

each overlayer having at least one alignment marking, each overlayer alignment marking corresponding to a different one of the underlayer alignment markings,

wherein alignment of overlayer alignment markings with corresponding underlayer alignment markings will align discrete locations of compressive pressure on the underlayer and each overlayer.

15. The multilayer compression stocking system of claim 14, each of the underlayer and overlayers having a length with proximal and distal portions, wherein the underlayer has pressure graduations along its length, each overlayer has pressure graduations along its length, and the pressure graduations along the length of each overlayer are the same as the pressure graduations along the length of the underlayer.

16. The multilayer compression stocking system of claim 15, wherein the amount of compressive pressure is greatest at a predetermined distal portion of each of the underlayer and overlayers so that the amounts of compressive pressure decrease from the predetermined distal portion to the proximal portion along the length of each of the underlayer and overlayers.

17. The multilayer compression stocking system of claim 14, wherein the predetermined amounts of compressive pressure comprise Class I, Class II, or Class III compressive pressures.

18. The multilayer compression stocking system of claim 14, wherein at least one of the underlayer and overlayers further comprises a toe portion having a high stretch modulus.

19. The multilayer compression stocking system of claim 18, at least one of the underlayer and overlayers having an instep portion, wherein each of the underlayer and overlayers having an instep portion further comprises a smooth construction from the toe portion to the instep portion.

20. The multilayer compression stocking system of claim 14, wherein each of the underlayer and overlayers further comprises a heel portion and one of the at least one alignment marking of each of the underlayer and overlayers is located on the heel portion.

21. The multilayer compression stocking system of claim 14, each of the underlayer and overlayers having a shape, wherein each of the underlayer and overlayers further comprises knit construction having the shape of the anatomy of the lower extremities.

22. The multilayer compression stocking system of claim 14, wherein at least one of the underlayer and overlayers further comprises construction having at least two-way stretch.
23. The multilayer compression stocking system of claim 14, wherein at least one of the underlayer and overlayers further comprises seamless construction.
24. The multilayer compression stocking system of claim 16, wherein one of the underlayer alignment markings and the corresponding overlayer alignment marking on each overlayer are located at the area of greatest compressive pressure.
25. The multilayer compression stocking system of claim 14, wherein the alignment markings comprise different colored yarns, a knit change, printing, and/or colored markings.
26. The multilayer compression stocking system of claim 14, one of the at least one overlayer being an outermost overlayer, wherein the outermost overlayer is colored to provide a cosmetic appearance.
27. The multilayer compression stocking system of claim 14, one of the at least one overlayer being an outermost overlayer, wherein the outermost overlayer is constructed to provide a cosmetic appearance.
28. The multilayer compression stocking system of claim 14, one of the at least one overlayer being an outermost overlayer, the system further comprising a non-compressive final outer layer for placement over the outermost overlayer.
29. The multilayer compression stocking system of claim 28, wherein the final outer layer is colored to provide a cosmetic appearance.
30. The multilayer compression stocking system of claim 28, wherein the final outer layer is constructed to provide a cosmetic appearance.
31. The multilayer compression stocking system of claim 15, wherein the length of at least one of the underlayer and overlayers is knee-length.
32. The multilayer compression stocking system of claim 18, wherein each of the underlayer and overlayers is joined in the toe portion.
33. A multilayer compression stocking system for use on a person's lower extremities, comprising:

an underlayer having predetermined amounts of compressive pressure at discrete locations on the underlayer;

at least one overlayer having predetermined amounts of compressive pressure at discrete locations on each overlayer;

5 each of the underlayer and overlayers having a length with proximal and distal portions, the underlayer having pressure graduations along its length, each overlayer having pressure graduations along its length;

the pressure graduations along the length of each overlayer are the same as the pressure graduations along the length of the underlayer;

10 the amount of compressive pressure is greatest at a predetermined distal portion of each of the underlayer and overlayers;

the amounts of compressive pressure decrease from the predetermined distal portion to the proximal portion along the length of each of the underlayer and overlayers;

15 the underlayer having at least one alignment marking, each underlayer alignment marking positioned at a different location on the underlayer; and

each overlayer having at least one alignment marking, each overlayer alignment marking corresponding to a different one of the underlayer alignment markings,

20 wherein alignment of overlayer alignment markings with corresponding underlayer alignment markings will align discrete locations of compressive pressure on the underlayer and each overlayer so that the portion of each of the underlayer and overlayers having the greatest compressive pressure and the same pressure graduations along the length of each of the underlayer and overlayers are aligned.

34. A method of applying a multilayer compression stocking system on a person's lower extremity, comprising:

25 positioning on the lower extremity a compressive pressure underlayer having at least one alignment marking, each underlayer alignment marking positioned at a different location on the underlayer and corresponding to a different anatomical location on the lower extremity;

30 aligning each underlayer alignment marking with the corresponding anatomical location on the lower extremity;

positioning over the underlayer at least one compressive pressure overlayer having at least one alignment marking, each overlayer alignment marking corresponding to a different one of the underlayer alignment markings; and

aligning each overlayer alignment marking with each corresponding underlayer alignment marking.

35. The method of applying a multilayer compression stocking system of claim 34, one of the at least one overlayer being an outermost overlayer, further comprising positioning a non-compressive final outer layer over the outermost overlayer.

36. The method of applying a multilayer compression stocking system of claim 34, wherein each of the underlayer and overlayers have predetermined amounts of compressive pressure at discrete locations.

37. The method of applying a multilayer compression stocking system of claim 36, wherein the predetermined amounts of compressive pressure of each of the underlayer and overlayers comprise Class I, Class II, or Class III compressive pressures.

38. The method of applying a multilayer compression stocking system of claim 34, each of the underlayer and overlayers having a length with proximal and distal portions, wherein the underlayer has pressure graduations along its length, each overlayer has pressure graduations along its length, and the pressure graduations along the length of each overlayer are the same as the pressure graduations along the length of the underlayer.

39. The method of applying a multilayer compression stocking system of claim 38, wherein the amount of compressive pressure is greatest at a predetermined distal portion of each of the underlayer and overlayers so that the amounts of compressive pressure decrease from the predetermined distal portion to the proximal portion along the length of each of the underlayer and overlayers.

40. The method of applying a multilayer compression stocking system of claim 39, wherein one of the underlayer alignment markings and one of the overlayer alignment markings on each overlayer are located at the area of greatest compressive pressure.

41. A method of applying a multilayer compression stocking system on a person's lower extremity, comprising:

providing an underlayer having predetermined amounts of compressive pressure at discrete locations and at least one alignment marking, each underlayer alignment marking

positioned at a different location on the underlayer and corresponding to a different anatomical location on the lower extremity;

positioning the underlayer on the lower extremity;

aligning each underlayer alignment marking with the corresponding anatomical location on the lower extremity;

providing at least one overlayer having predetermined amounts of compressive pressure at discrete locations and having at least one alignment marking, each overlayer alignment marking corresponding to a different one of the underlayer alignment markings, each of the underlayer and overlayers having a length with proximal and distal portions, the underlayer having pressure graduations along its length, each overlayer having pressure graduations along its length, the pressure graduations along the length of each overlayer being the same as the pressure graduations along the length of the underlayer, the amount of compressive pressure being greatest at a predetermined distal portion of each of the underlayer and overlayers so that the amounts of compressive pressure decrease from the predetermined distal portion to the proximal portion along the length of each of the underlayer and overlayers;

positioning one of the at least one overlayer over the underlayer; and

aligning each overlayer alignment marking with each corresponding underlayer alignment marking.

42. A multilayer compression stocking system for use on a person's lower extremities, comprising:

a plurality of layers including an underlayer and at least one overlayer;

at least one of the layers having predetermined amounts of compressive pressure at discrete locations on the layer;

the underlayer having at least one alignment marking, each underlayer alignment marking positioned at a different location on the underlayer;

the overlayer having at least one alignment marking, each overlayer alignment marking corresponding to a different one of the underlayer alignment markings; and

the underlayer having a top, the overlayer having a top and a bottom, and the overlayer bottom foldably attached to the underlayer top,

wherein downwardly folding the overlayer over the underlayer to align overlayer alignment markings with corresponding underlayer alignment markings will align discrete locations of compressive pressure on the underlayer and the overlayer.

43. The multilayer compression stocking system of claim 42, wherein the underlayer and the overlayer each have predetermined amounts of compressive pressure at discrete locations on the layer.

44. The multilayer compression stocking system of claim 42, each of the underlayer and overlayer having a length with proximal and distal portions, wherein the underlayer has pressure graduations along its length, the overlayer has pressure graduations along its length, and the pressure graduations along the length from the distal portion to the proximal portion of the overlayer are the same as the pressure graduations along the length from the distal portion to the proximal portion of the underlayer.

45. The multilayer compression stocking system of claim 44, wherein the amount of compressive pressure is greatest at a predetermined distal portion of each of the underlayer and overlayer so that the amounts of compressive pressure decrease from the predetermined distal portion to the proximal portion along the length of each of the underlayer and overlayer.

46. The multilayer compression stocking system of claim 42, wherein the predetermined amounts of compressive pressure of each of the underlayer and overlayer comprise of Class I, Class II, or Class III compressive pressures.

47. The multilayer compression stocking system of claim 42, wherein at least one of the underlayer and overlayers further comprises a toe portion having a high stretch modulus.

48. The multilayer compression stocking system of claim 47, the underlayer having an instep portion, wherein the underlayer further comprises a smooth construction from the toe portion to the instep portion.

49. The multilayer compression stocking system of claim 42, wherein the underlayer further comprises a heel portion and one of the at least one alignment marking of the underlayer is located on the heel portion.

50. The multilayer compression stocking system of claim 42, each of the underlayer and overlayer having a shape, wherein the underlayer further comprises knit construction having the shape of the anatomy of the lower extremities.

51. The multilayer compression stocking system of claim 42, wherein at least one of the underlayer and overlayer further comprises construction having at least two-way stretch.

52. The multilayer compression stocking system of claim 42, wherein at least one of the underlayer and overlayer further comprises seamless construction.

53. The multilayer compression stocking system of claim 42, wherein one of the underlayer alignment markings and the corresponding overlayer alignment marking are located at the area of greatest compressive pressure.

54. The multilayer compression stocking system of claim 42, wherein the underlayer alignment markings and the overlayer alignment markings comprise different colored yarns, a knit change, printing, and/or colored markings.

55. The multilayer compression stocking system of claim 42, wherein the overlayer is colored to provide a cosmetic appearance.

56. The multilayer compression stocking system of claim 42, wherein the overlayer is constructed to provide a cosmetic appearance.

57. The multilayer compression stocking system of claim 55, wherein the colored overlayer further comprises construction to provide a cosmetic appearance.

58. The multilayer compression stocking system of claim 43, wherein the length of at least one of the underlayer and overlayer is knee-length.

59. A multilayer compression stocking system for use on a person's lower extremities, comprising:

an underlayer having predetermined amounts of compressive pressure at discrete locations on the underlayer;

an overlayer having predetermined amounts of compressive pressure at discrete locations on the overlayer;

each of the underlayer and overlayer having a length with proximal and distal portions, the underlayer having pressure graduations along its length, the overlayer having pressure graduations along its length;

the pressure graduations along the length from the distal portion to the proximal portion of the overlayer are the same as the pressure graduations along the length from the distal portion to the proximal portion of the underlayer;

the amount of compressive pressure is greatest at a predetermined distal portion of each of the underlayer and overlayer;

the amounts of compressive pressure decrease from the predetermined distal portion to the proximal portion along the length of each of the underlayer and overlayer;

the underlayer having at least one alignment marking, each underlayer alignment marking positioned at a different location on the underlayer;

the overlayer having at least one alignment marking, each overlayer alignment marking corresponding to a different one of the underlayer alignment markings; and

the underlayer having a top, the overlayer having a top and a bottom, and the overlayer bottom foldably attached to the underlayer top,

wherein downwardly folding the overlayer over the underlayer to align overlayer alignment markings with corresponding underlayer alignment markings will align discrete locations of compressive pressure on the underlayer and the overlayer so that the portion of each of the underlayer and overlayer having the greatest compressive pressure and the same pressure graduations along the length of each of the underlayer and overlayer are aligned.

60. A method of applying a multilayer compression stocking system on a person's lower extremity, comprising:

providing a compressive pressure underlayer having a top and at least one alignment marking, each underlayer alignment marking positioned at a different location on the underlayer and corresponding to a different anatomical location on the lower extremity;

positioning the compressive pressure underlayer on the lower extremity;

aligning each underlayer alignment marking with the corresponding anatomical location on the lower extremity;

providing a compressive pressure overlayer having a top, a bottom, the overlayer bottom foldably attached to the underlayer top, and at least one alignment marking, each

overlayer alignment marking corresponding to a different one of the underlayer alignment markings;

downwardly folding the overlayer over the underlayer; and

aligning each overlayer alignment marking with each corresponding underlayer

alignment marking.

61. The method of applying a multilayer compression stocking system of claim 60, wherein at least one of the underlayer and overlayer has predetermined amounts of compressive pressure at discrete locations.

62. The method of applying a multilayer compression stocking system of claim 61, wherein the predetermined amounts of compressive pressure comprise Class I, Class II, or Class III compressive pressures.

63. The method of applying a multilayer compression stocking system of claim 60, each of the underlayer and overlayer having a length with proximal and distal portions, wherein the underlayer has pressure graduations along its length, the overlayer has pressure graduations along its length, and the pressure graduations along the length from the distal portion to the proximal portion of the overlayer are the same as the pressure graduations along the length from the distal portion to the proximal portion of the underlayer.

64. The method of applying a multilayer compression stocking system of claim 63, wherein the amount of compressive pressure is greatest at a predetermined distal portion of each of the underlayer and overlayer so that the amounts of compressive pressure decrease from the predetermined distal portion to the proximal portion along the length of each of the underlayer and overlayer.

65. The method of applying a multilayer compression stocking system of claim 64, wherein one of the underlayer alignment markings and the corresponding overlayer alignment marking are located at the area of greatest compressive pressure.

66. A method of applying a multilayer compression stocking system on a person's lower extremity, comprising:

providing a compressive pressure underlayer having a top, predetermined amounts of compressive pressure at discrete locations, and at least one alignment marking, each

underlayer alignment marking positioned at a different location on the underlayer and corresponding to a different anatomical location on the lower extremity;

positioning the underlayer on the lower extremity;

5 aligning each underlayer alignment marking with the corresponding anatomical location on the lower extremity;

providing a compressive pressure overlayer having a top, a bottom, the overlayer bottom foldably attached to the underlayer top, at least one alignment marking, each overlayer alignment marking corresponding to a different one of the underlayer alignment markings, and predetermined amounts of compressive pressure at discrete locations, each
10 of the underlayer and overlayer having a length with proximal and distal portions, the underlayer having pressure graduations along its length, the overlayer having pressure graduations along its length, the pressure graduations along the length from the distal portion to the proximal portion of the overlayer are the same as the pressure graduations along the length from the distal portion to the proximal portion of the underlayer, the
15 amount of compressive pressure being greatest at a predetermined distal portion of each of the underlayer and overlayer so that the amounts of compressive pressure decrease from the predetermined distal portion to the proximal portion along the length of each of the underlayer and overlayer;

downwardly folding the overlayer over the underlayer; and

20 aligning each overlayer alignment marking with each corresponding underlayer alignment marking.

67. A multilayer compression bandage system comprising:

an underlayer having predetermined amounts of compressive pressure at discrete locations on the underlayer;

25 at least one overlayer having predetermined amounts of compressive pressure at discrete locations on each overlayer;

the underlayer having at least one alignment marking, each underlayer alignment marking positioned at a different location on the underlayer; and

each overlayer having at least one alignment marking, each overlayer alignment
30 marking corresponding to a different one of the underlayer alignment markings,

wherein alignment of overlayer alignment markings with corresponding underlayer alignment markings will align discrete locations of compressive pressure on the underlayer and each overlayer.

68. The multilayer compression bandage system of claim 67, wherein each of the
5 underlayer and overlayers having a length with proximal and distal portions, and wherein the underlayer has pressure graduations along its length, each overlayer has pressure graduations along its length, and the pressure graduations along the length of each overlayer are the same as the pressure graduations along the length of the underlayer.

69. The multilayer compression bandage system of claim 68, wherein the amount of
10 compressive pressure is greatest at a predetermined distal portion of each of the underlayer and overlayers so that the amounts of compressive pressure decrease from the predetermined distal portion to the proximal portion along the length of each of the underlayer and overlayers.

70. The multilayer compression bandage system of claim 67, wherein the
15 predetermined amounts of compressive pressure comprise Class I, Class II, and Class III compressive pressures.




FIG. 1




FIG. 2




FIG. 3




FIG. 4

INTERNATIONAL SEARCH REPORT

International Application No

PCT/US 00/17213

A. CLASSIFICATION OF SUBJECT MATTER
IPC 7 A61F13/08

According to International Patent Classification (IPC) or to both national classification and IPC

B. FIELDS SEARCHED

Minimum documentation searched (classification system followed by classification symbols)

IPC 7 A61F

Documentation searched other than minimum documentation to the extent that such documents are included in the fields searched

Electronic data base consulted during the international search (name of data base and, where practical, search terms used)

EPO-Internal

C. DOCUMENTS CONSIDERED TO BE RELEVANT

Category *	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
X	FR 2 432 867 A (THUASNE & CIE) 7 March 1980 (1980-03-07)	1,2,5-7, 9-17, 20-27, 31,33, 34, 36-41,67
A	page 1, line 1 - line 32 page 2, line 17 -page 6, line 15 claims 1,2,5; figures 1-7 --- -/--	42,60-66

☒ Further documents are listed in the continuation of box C.

☒ Patent family members are listed in annex.

* Special categories of cited documents:

A document defining the general state of the art which is not considered to be of particular relevance

E earlier document but published on or after the international filing date

L document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified)

O document referring to an oral disclosure, use, exhibition or other means

P document published prior to the international filing date but later than the priority date claimed

T later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention

X document of particular relevance: the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone

Y document of particular relevance: the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art.

& document member of the same patent family

Date of the actual completion of the international search

20 November 2000

Date of mailing of the international search report

30/11/2000

Name and mailing address of the ISA

European Patent Office, P.B. 5818 Patentlaan 2
NL - 2280 HV Rijswijk
Tel. (+31-70) 340-2040. Tx. 31 651 epo nl.
Fax: (+31-70) 340-3016

Authorized officer

Joly, F

INTERNATIONAL SEARCH REPORT

International Application No.

PCT/US 00/17213

C.(Continuation) DOCUMENTS CONSIDERED TO BE RELEVANT

Category *	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
X	FR 2 749 754 A (INNOTHERA TOPIC INTERNATIONAL) 19 December 1997 (1997-12-19) page 1, line 27 -page 2, line 31 page 3, line 21 -page 5, line 16; claims 1,5; figures 1-7 ---	1,2,5-7, 9-17,20, 21,23, 26,33, 34, 36-41,67
X	US 5 836 904 A (COOPER CURTIS R) 17 November 1998 (1998-11-17) column 1, line 58 -column 2, line 15 column 3, line 50 -column 6, line 33 figures 1-5 ---	1,2,6,7, 9-12,14, 15,21, 23, 25-27, 34,38, 39,42, 44-46, 50,52, 54-57, 60,63,67
X	WO 98 51247 A (JONES TIM ;PRIEST MARK (GB); SCARFE JULIAN (GB); AGER COLIN (GB);) 19 November 1998 (1998-11-19) cited in the application page 1, line 16 -page 3, line 24 page 4, line 1 - line 26 page 6, line 12 -page 7, line 9 page 8, line 1 -page 10, line 2 figures 1-4C; example 4 ---	9,11,13, 67
X	US 3 613 679 A (BIJOU PATRICIA W) 19 October 1971 (1971-10-19) column 1, line 13 - line 40 column 2, line 1 - line 32 figures 1-8 ---	9-13
A	GB 2 322 566 A (CHAMPION LAB INC) 2 September 1998 (1998-09-02) figures 1-6 ---	1-70
A	US 4 308 864 A (SMALL MARTIN H ET AL) 5 January 1982 (1982-01-05) figures 1-3 ---	28,42,60
A	US 5 310 402 A (ROLLBAND ERNEST J) 10 May 1994 (1994-05-10) column 4, line 35 -column 5, line 17 figures 1-8 -----	9

INTERNATIONAL SEARCH REPORT

Information on patent family members

International Application No

PCT/US 00/17213

Patent document cited in search report		Publication date	Patent family member(s)	Publication date
FR 2432867	A	07-03-1980	NONE	
FR 2749754	A	19-12-1997	AU 3348097 A BR 9710851 A CA 2258119 A EP 0927014 A WO 9747262 A PL 330427 A	07-01-1998 11-01-2000 18-12-1997 07-07-1999 18-12-1997 10-05-1999
US 5836904	A	17-11-1998	NONE	
WO 9851247	A	19-11-1998	AU 7345898 A EP 0984755 A ZA 9803953 A	08-12-1998 15-03-2000 10-11-1998
US 3613679	A	19-10-1971	NONE	
GB 2322566	A	02-09-1998	US 5772881 A DE 19781179 T JP 2000503257 T CA 2238652 A WO 9819767 A	30-06-1998 05-11-1998 21-03-2000 14-05-1998 14-05-1998
US 4308864	A	05-01-1982	NONE	
US 5310402	A	10-05-1994	US 5213565 A	25-05-1993